

Extra Heavy Duty Industrial

Gold Line

All Gold Line HD industrial fans are complete with corrosion resistant epoxy-coated aluminum blades.

*specified for
airport
hangers*

save

up to
50% of your cooling cost
30% of your heating cost



new
heavy duty
CAST YOKE
for easy infield downrod change

Gold



ideal
for extra heavy duty industrial use

- rugged industrial application
- ideal for high ceilings
- longer life
- the fan specified most by engineers!

Model	160F7-10	160F7-10BR	160F7-10BK	160F7-220V	160C7-10*	136F-10	136C-10
Safety Cable	38" - 39"	38" - 39"	38" - 39"	38" - 39"	38" - 39"	38" - 39"	38" - 39"
Cord/Lead Wire	16"	16"	16"	16"	16"	16"	16"
Diameter Sweep	56"	56"	56"	56"	56"	36"	36"
CFM	34,500	34,500	34,500	34,500	34,500	12,000	12,000
Area (sq.ft.)	2,100	2,100	2,100	2,100	2,100	800	800
Velocity (ft/m)	650	650	650	650	650	650	650
Volts	120	120	120	220-240	120	120	120
Amps	0.70	0.70	0.70	0.37	0.70	0.36	0.36
Watts	75	75	75	75	75	35	35
RPM (max)	320	350	350	350	350	400	400
Wiring	plug-in	plug-in	plug-in	2+ground	3+ground	plug-in	3+ground
Airflow	down only	down only	down only	down only	up & down	down only	up & down
Weight	24 lbs	24 lbs	24 lbs	24 lbs	24 lbs	17 lbs	17 lbs

*straight blade model

Gold features

- Downrod diameter 1" eg. E961-36
- Corrosion-resistant epoxy prime and finish coat on all metal housing & blade.
The aerodynamically curved-tip **aluminum blade** results in maximum air delivery.
- Customized downrod lengths over 36" available. Also 16' cord with plug part# Cord-Wh16.
- Pre-wired with 16" cord and built-in strain relief
- Use solid state infinite speed motor controls or church quiet control for one fan only (WC103)
- 9.5 mfd non-polar, weatherproof encapsulated, extra heavy-duty capacitor. (136F-10 has 4.0 uf capacitor)
- Permanent lubricated sealed TPI ball bearings.
- All metal, no plastic.
- Totally enclosed impedance protected cast motor.
- High grade cool steel motor laminations for maximum energy efficiency & heat dissipation for longer life.

