

Air Circulation

Aluminum Shutters

- Aluminum Powered Intake Shutters or free-air exhaust
- Nylons bearings; solid shafts; drawn cup-type sleeves on all movable linkage
- Frame of heavy aluminum extrusion with 1/2" channel lock water stop and precision milled corners
- Interlocking blades for maximum weather seal
- Double panel units constructed with rigid "T" section center member



Part #	Size	Description
VRSG16A-C	16" x 16"	
VRSG20A-C	20" x 20"	
VRSG24A-C	24" x 24"	
VRSG30A-C	30" x 30"	
VRSG36A-C	36" x 36"	
VRSG42A-C	42" x 42"	
VRSG48A-C	48" x 48"	
VRSG54A-C	54" x 54"	
VRSG60A-C	60" x 60"	
VRS1230-C		Motorized shutter kit: 12"-30", with cord
VRS3660-C		Motorized shutter kit: 36"-60", with cord

Poly Shutters

Constructed of a white exterior grade PVC material to create a maintenance free shutter. No rust, no corrosion, never needs painting and easy to clean. Improved fan efficiency has been achieved through our aerodynamic design which creates smoother operation and less air drag.

- Stainless steel corner clips inside PVC framework, results in stronger shutter construction
- Nylon pivot bearing on each louver
- Curved shape of the blades assures a tight seal when the shutter is closed



Part #	Size
VRS12P	12" x 12"
VRS16P	16" x 16"
VRS20P	20" x 20"
VRS24P	24" x 24"
VRS30P	30" x 30"
VRS36P	36" x 36"
VRS42P	42" x 42"
VRS48P	48" x 48"
VRS54P	54" x 54"

1-888-82-BANVIL • FAX 1-888-422-6845