

Air Circulation

ES Shutter Fan Exhaust Fans



Control Flow VENTILATING FANS :

- Distribute fresh air throughout building.
- Control wide temperature ranges.
- Control condensation.
- Remove gases, moisture and bad odors.
- Improve air quality.
- Improve profits.



MOTOR—Thermally protected PSC Motor (air over) is totally enclosed and designed for a continuous duty work load. Totally Enclosed, U.L.C. listed motors. *Two year warranty.*

BLADE—The fan blade is constructed of aluminum with a zinc plated steel hub balanced for smooth vibration-free operation. Pitch is designed to correlate with motor horsepower to deliver maximum efficiency.

CHROME GRILL—Allows easy cleaning and meets OSHA guidelines. Allows easy cleaning and meets OSHA guidelines. (OSHA approved on interior wall and approved on exterior wall when mounted 7' above ground.)

SHUTTER—High efficiency aluminum shutters.

Part #	Size	Drive	HP	RPM	Spd	Phs	Volt	CFM	AMPS
VES12	12"	DD	1/12	1750	S/V-SP	1	115	1,050	1.0/.5
VES16	16"	DD	1/4	1750	S/V-SP	1	115	2,175	3.0
VES20	20"	DD	1/4	1750	S/V-SP	1	115	3,575	3.0
VES24	24"	DD	1/2	1750	S/V-SP	1	115	6,125	3.5/1.7

1-888-82-BANVIL • FAX 1-888-422-6845