

## Air Circulation



Cone Fan  
Slant wall



# Typhoon Exhaust Fans

## Cone and No-cone Models

- Heavy Duty Galvanized Box Fan
- Galvanized Venturi and X-Frame
- Galvanized Wire Mesh Guard
- Industrial Grade Aluminum Shutter
- Automatic spring loaded belt tightener
- Energy Efficient Motors
- Totally Enclosed, U.L.C. listed motors (Except 42" Models)
- **Two Year Motor Warranty**
- Prelubricated ball bearings, thermal overload protection

The 48" Typhoon Cone Fan has been tested and certified by an independent testing agency. Our galvanized Scallop-Twist designed blade is engineered for high output-low noise. The energy efficient, thermally protected, totally enclosed ball bearing motor has a **2 year warranty**.

*Please note when installing a Typhoon fan you must also supply an inlet. We recommend our power intake shutters. Generally you should order one shutter per fan at least one size larger than your fan.*

### FAN HOUSING:

- Cost efficient heavy duty 18 gauge galvanized construction for superior durability and longevity. Smooth spun venturi maximize air-flow dynamics.
- Galvanized blade is engineered for high output-low noise.
- Galvanized Deep Cone to reduce back pressure and boost performance.
- Heavy duty galvanized X-Frame motor mount provides solid motor mounting for increased motor life and quieter operation.

### FAN BLADES:

Galvanized three and four blade props; highly efficient, easy cleaning, balanced for smooth operation and extended life of blade and motor.

**NEW** cast aluminum 50" blades for high performance and low noise.

### MOTOR:

- Tough, energy efficient, totally enclosed, automatic thermal protection, pre-lubricated ball bearings, dual voltage.
- Totally Enclosed, U.L.C. listed motors
- **2-Year warranty.**
- Heavy Duty Automatic belt tightener on all belt drive models.
- Matched motor & belt ratio for maximum air, without overloading the motor.
- Eccentric lock collar bearings.

### SHUTTERS:

High performance aluminum shutters.



No-cone  
Slant wall

**1-888-82-BANVIL • FAX 1-888-422-6845**